Steward® | K-4918

Half-stall waterless urinal

Features

- Cartridge-free waterless urinal functionality
- Saves up to 40,000 gallons of water per fixture per year and significantly reduces sewage and maintenance costs
- Cartridge-free integral trapway provides enhanced performance and less maintenance
- Optimized interior design virtually eliminates splashing
- Touch-free design is vandal resistant and offers added hygiene to users
- This product can help a building earn Water Efficiency points in LEED® Green Building Rating System



Available Colors/Finishes

Color tiles intended for reference only.

7 Black Black

1-800-4KOHLER (1-800-456-4537)
Kohler Co. reserves the right to make revisions without notice to product specifications.
For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.
8-06-2026 13:01 - US-CA

Codes/Standards

ADA compliant when installed to the specific requirements of these regulations.

ADA

ASME A112.19.2/CSA B45.1
ADA
ICC/ANSI A117.1

Technical Information

All product dimensions are nominal.

Spud Size:	2", Outlet, Rear
Trapway Type:	Concealed

Material

- Vitreous china

Included Components

Recommended Products/Accessories

1048656 Sealing liquid (1 Gallon)

1048656-P Waterless Urinal Sealing Liquid- Case

1174866 3-Pack Waterless Urinal Cleaner

K-4929 Waterless urinal maintenance balls

Warranty

See website for detailed warranty information.

KOHLER® One-Year Limited Warranty

1-800-4KOHLER (1-800-456-4537)
Kohler Co. reserves the right to make revisions without notice to product specifications.
For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.
8-06-2026 13:01 - US-CA

THE BOLD LOOK OF KOHLER.

Installation

- 29-5/8" H x 15" W x 15-5/8" D

Installation Notes

Install this product according to the installation instructions.

CAUTION: Risk of property damage. When connecting waterless urinals to the building drain waste vent system, do not use copper pipe or copper tube connectors. The use of a copper connector will result in corrosion of the connector and potential building structure damage caused by leakage.
Product dimensions are nominal and may vary per ASME A112.19.2 tolerances.
ADA compliant when installed to the specific requirements of these regulations.

1-800-4KOHLER (1-800-456-4537)
Kohler Co. reserves the right to make revisions without notice to product specifications.
For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.
8-06-2026 13:01 - US-CA

THE BOLD LOOK OF KOHLER.